


















Technische Daten für Muldenvarianten Typ: MUK303

1. **Laderaumvolumen m<sup>3</sup>**

		Muldenlänge				
mm		5.200	6.000	6.500	7.000	7.500
Höhe	1.480 ↓	 17,50 m <sup>3</sup>	 20,50 m <sup>3</sup>	 22,00 m <sup>3</sup>	 23,50 m <sup>3</sup>	 25,50 m <sup>3</sup>
	1.730 ↓	 20,50 m <sup>3</sup>	 23,50 m <sup>3</sup>	 25,50 m <sup>3</sup>	 27,50 m <sup>3</sup>	 29,50 m <sup>3</sup>
	1.950 ↓	 23,00 m <sup>3</sup>	 26,50 m <sup>3</sup>	 29,00 m <sup>3</sup>	 30,50 m <sup>3</sup>	 33,50 m <sup>3</sup>
	2.200 ↓	 26,00 m <sup>3</sup>	 30,00 m <sup>3</sup>	 32,50 m <sup>3</sup>	 35,00 m <sup>3</sup>	 37,50 m <sup>3</sup>
<b>mit Bordwandaufsatz</b>						
Höhe	1.980 ↓ (1.480 + 500)	 23,50 m <sup>3</sup>	 27,00 m <sup>3</sup>	 29,50 m <sup>3</sup>	 31,50 m <sup>3</sup>	 34,00 m <sup>3</sup>
	2.280 ↓ (1.480 + 800)	 27,00 m <sup>3</sup>	 31,00 m <sup>3</sup>	 34,00 m <sup>3</sup>	 36,50 m <sup>3</sup>	 39,00 m <sup>3</sup>
	2.230 ↓ (1.730 + 500)	 26,50 m <sup>3</sup>	 30,50 m <sup>3</sup>	 33,00 m <sup>3</sup>	 35,50 m <sup>3</sup>	 38,00 m <sup>3</sup>
	2.450 ↓ (1.950 + 500)	 29,00 m <sup>3</sup>	 33,50 m <sup>3</sup>	 36,00 m <sup>3</sup>	 39,00 m <sup>3</sup>	 41,50 m <sup>3</sup>

2. **Ölbedarf Kippzylinder**

		Muldenlänge				
mm	5200	6000	6500	7000	7500	
Ölbedarf ca.	30,6 l	32,5 l	34,4 l	34,4 l	34,4 l	
Für jede weitere doppelwirkende Funktion (1 Zylinder) ca. 1 l						