













Technische gegevens voor bakvarianten type: MUK303

1. **Volume laadruimte m³**

		Lengte bak				
mm		5.200	6.000	6.500	7.000	7.500
Hoogte	1.480 ↓	 17,50 m ³	 20,50 m ³	 22,00 m ³	 23,50 m ³	 25,50 m ³
	1.730 ↓	 20,50 m ³	 23,50 m ³	 25,50 m ³	 27,50 m ³	 29,50 m ³
	1.950 ↓	 23,00 m ³	 26,50 m ³	 29,00 m ³	 30,50 m ³	 33,50 m ³
	2.200 ↓	 26,00 m ³	 30,00 m ³	 32,50 m ³	 35,00 m ³	 37,50 m ³
met boordwandverhoging						
Hoogte	1.980 ↓ (1.480 + 500)	 23,50 m ³	 27,00 m ³	 29,50 m ³	 31,50 m ³	 34,00 m ³
	2.280 ↓ (1.480 + 800)	 27,00 m ³	 31,00 m ³	 34,00 m ³	 36,50 m ³	 39,00 m ³
	2.230 ↓ (1.730 + 500)	 26,50 m ³	 30,50 m ³	 33,00 m ³	 35,50 m ³	 38,00 m ³
	2.450 ↓ (1.950 + 500)	 29,00 m ³	 33,50 m ³	 36,00 m ³	 39,00 m ³	 41,50 m ³

2. **Olieverbruik kipcilinder**

		Lengte bak				
mm	5200	6000	6500	7000	7500	
Olieverbruik ca.	30,6 l	32,5 l	34,4 l	34,4 l	34,4 l	

Voor elke verdere dubbelwerkende functie (1 cilinder) ca. 1 l